

C A T A L O G U E

# TECHNICAL CLEANING PRODUCTS FOR ALL PROFESSIONAL VEHICLES



# TRANSNET



THE ONLY FRENCH MANUFACTURER VERTICALLY  
INTEGRATED FROM DESIGN TO MARKETING

# THE STRENGTH OF AN INDUSTRIAL GROUP

ORAPI's production and logistics are entrusted to those who constantly strive to enhance product quality and customer satisfaction, with one shared requirement: care of the environment.



## RESEARCH AND DEVELOPMENT

A research laboratory and a regulatory department constantly designing and adapting formulas and labelling to the new regulatory chemical standards.

## PRODUCTION PLANT

All our products are manufactured in our plant near Lyon. Our site is ISO 9001 and 14001 certified.



## IN FRANCE AND ABROAD

Sales and technical teams, genuine local experts to respond to all your needs.

## ON THE INTERNATIONAL STAGE

More than 2 million users worldwide

# SUMMARY



## **EXTERIOR SHAMPOOS**

---

p.4-5

## **TECHNICAL CLEANING FOOD RANGE**

---

p.6-7

## **DEGREASERS**

---

p.8-9

## **RENOVATORS**

---

p.10-11

## **TAR REMOVING**

---

p.11

## **WORKSHOP**

---

p.12

## **WASH STATION MAINTENANCE**

---

p.13-14

## **MATERIALS**

---

p.15-17

## PLATINIUM

05050

### SUPER ACTIVE SHAMPOO

Super concentrated shampoo that easily removes traffic film and the various soils encountered on the bodies (insects, grease ...) without affecting paints and varnishes or application equipment. Facilitates the removal of all grease, dirt ... and has an active dense foam increasing the contact time and therefore detergency. Given its special formulation, it is as effective on the body as well as it is on the tarpaulin for truck trailers, public works, transport... and has an easy rinse.

Operating temperature	40°C
Dosage	2 to 5 % (manual use) 0,5 to 1 % (roll-over vehicle wash system)
Application time	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN050500447	drum	25 kg
TN050500450	drum	220 kg
TN050500483	container	1050 kg



## C SUPER

05060

### SHAMPOO WITH REINFORCED ACTION

Concentrated anti-static shampoo. Effective for removing grease and insects. Works well even without scrubbing. Removes road film. For roll-over vehicle brush wash systems, foam cannons, etc.

Operating temperature	40°C
Dosage	2 to 5 % (manual use) 0,5 to 1 % (roll-over brush vehicle wash system)
Application time	3 to 5 min

REFERENCE	PACKAGING	WEIGHT
TN050600441	jerrycan	5 kg
TN050600447	drum	25 kg
TN050600451	drum	70 kg
TN050600450	drum	240 kg
TN050600483	container	1150 kg

## C +

05300

### WATER-REPELLENT SHAMPOO

Ultra-powerful anti-static shampoo which is water-repellent and effective at removing Insects. Works well without scrubbing. Leaves a long-lasting shiny film. For roll-over vehicle wash system, washing by hand, foam cannons, etc.

Operating temperature	40°C
Dosage	2 to 5 % (manual use) 0,5 to 1 % (roll-over vehicle wash system)
Application time	3 to 5 min

REFERENCE	PACKAGING	WEIGHT
TN053000441	jerrycan	5 kg
TN053000447	drum	25 kg
TN053000450	drum	230 kg
TN053000483	container	1100 kg

## S +

0506W

### SCENTED SHAMPOO

New-generation shampoo for all vehicles. Removes road film while leaving a shiny film on the vehicle body.

Operating temperature	40°C
Dosage	3 to 6 %
Application time	3 to 5 min

REFERENCE	PACKAGING	WEIGHT
TN0506W0441	jerrycan	5 kg
TN0506W0447	drum	25 kg
TN0506W0451	drum	60 kg
TN0506W0450	drum	240 kg
TN0506W0483	container	1150 kg

## SGC

05400

### CLASSIC SHAMPOO

Bodywork shampoo for all vehicles. Removes road film.

Operating temperature	40°C
Dosage	5 to 8 % (manual use)
Application time	3 to 5 min

REFERENCE	PACKAGING	WEIGHT
TN054000441	jerrycan	5 kg
TN054000447	drum	24 kg
TN054000450	drum	220 kg
TN054000483	container	1050 kg

# S

05409

## STANDARD SHAMPOO

Body shampoo for use on all vehicles.  
Leaves a shiny film on the vehicle body.

Operating temperature	< 50°C
Dosage	4 to 8 %
Application time	5 min

REFERENCE	PACKAGING	WEIGHT
TN054090447	drum	24 kg
TN054090450	drum	220 kg
TN054090483	container	1050 kg

# SCM

05169

## DEGREASING SHAMPOO

Body shampoo, powerful high foaming detergent  
Particularly suitable for vehicles and parts in case of important staining.

Operating temperature	< 40°C (50°C for mechanical parts)
Dosage	3 to 8 % (bodywork) 15 to 30 % (tarpaulins, chassis, engines)
Application time	5 to 10 min

REFERENCE	PACKAGING	WEIGHT
TN051690441	jerrycan	5 kg
TN051690447	drum	25 kg
TN051690450	drum	230 kg
TN051690483	container	1100 kg



SHAMPOOS

# TAM

01171

## RENOVATING ACID SHAMPOO

Phosphorous free, readily biodegradable, waste treated by water treatment plants or bioreactors. Removes rust and all traces of oxidation. Specially formulated for trams, underground trains, trains, buses and coaches, etc.

Operating temperature	40°C
Dosage	10 to 20 % (LP spray or roll-over brushes)
Application time	3 to 5 min

REFERENCE	PACKAGING	WEIGHT
TN011710441	jerrycan	5 kg
TN011710446	drum	22 kg
TN011710450	drum	260 kg



# TS

05032

## NEUTRAL SHAMPOO

Gentle pH neutral detergent shampoo. Prevents the formation of limescale. Non foaming, scented. For washing by hand, in an automatic vehicle washer or in a roll-over vehicle brush wash system.

Operating temperature	60°C
Dosage	2 to 5 % (roll-over vehicle brush wash system)
Application time	5 min

REFERENCE	PACKAGING	WEIGHT
TN050320441	jerrycan	5 kg
TN050320447	drum	23 kg
TN050320450	drum	200 kg
TN050320483	container	1000 kg

# PROCAR AT

C441

## SPECIAL HIGH PRESSURE

Concentrated shampoo for high pressure cleaners and washing machines of mechanical parts. Suitable for painted surfaces and sensitive metals such as aluminum ... Low foaming, easy to rinse, does not leave any trace, for the washing of the bodies, construction equipment, agricultural machinery ... neutral pH.

REFERENCE	PACKAGING	VOLUME
C441/0210	drum	210 kg

# TECHNICAL CLEANING - FOOD RANGE

## NVA

05600

### FOOD-GRADE SHAMPOO, LASTING SHINE

Cleaner for food vehicles such as tanks or refrigerated trucks. Provides effective washing before the disinfection step. Enriched formula that provides lasting shine.

Operating temperature	< 40°C
Dosage	3 to 6 %
Application time	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN056000447	drum	25 kg
TN056000450	drum	230 kg
TN056000483	container	1100 kg

## NVA +

051U0

### CONCENTRATED FOOD-GRADE SHAMPOO

Concentrated anti-static shampoo. Interior and exterior washing of vehicles used to transport foodstuffs. Dye and fragrance free. Leaves a high shine after application. Suitable for wash heads (CIP).

Operating temperature	45°C
Dosage	3 to 5 % (LP spray) 0,5 à 1 % (roll-over brushes)
Application time	3 to 15 min



REFERENCE	PACKAGING	WEIGHT
TN051U00447	drum	25 kg
TN051U00450	drum	220 kg
TN051U00483	container	1085 kg



## SA

05604

### INTERIOR AND EXTERIOR SHAMPOO

Food grade shampoo for tanks, refrigerated trucks. Interior/external wash that leaves a correct shine before the disinfection step.

Operating temperature	< 50°C
Dosage	4 to 6 %
Application time	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN056040441	jerrycan	5 kg
TN056040448	drum	25 kg
TN056040450	drum	230 kg

## SA +

051V0

### REINFORCED SHAMPOO

Food shampoo for indoor and outdoor cleaning of fridges, cisterns ...  
Brilliance enhanced after application.

Operating temperature	< 40°C
Dosage	2 to 5 %
Application time	5 to 10 min



REFERENCE	PACKAGING	WEIGHT
TN051V00441	jerrycan	5 kg
TN051V00450	drum	220 kg

## LC

05300

### STANDARD FOOD SHAMPOO

Alkaline detergent for all surfaces: bodies, tarpaulins, side panels, bins ...  
Foaming, has no phosphates or solvents, perfectly suited for the food industry.  
Allows you to remove road film, grease...

Température d'utilisation	< 40°C
Dosage	5 to 10 %
Temps de contact	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN053M00447	drum	23 kg
TN053M00450	drum	210 kg
TN053M00483	container	1000 kg

# BACTIMOUSS 02089

## FOAMING DISINFETANT

Foaming bactericide and fungicide disinfecting detergent. For the interior of refrigerated lorries and food cisterns. Removes tannins and traces of blood. Removes heavy soil from painted floors.

Operating temperature	35°C
Dosage	4 to 6 % (LP spray or foam cannon)
Application time	15 to 20 min



REFERENCE	PACKAGING	WEIGHT
TN020890441	jerrycan	5 kg
TN020890447	drum	25 kg
TN020890450	drum	230 kg
TN020890483	container	1150 kg

Biocide regulation n°528/2012 - N°MEEDDM : 12550

# DDA

02009

## NON-FOAMING DISINFECTANT

Non-foaming bactericide and fungicide\* detergent. Chlorinated product for use inside refrigerated lorries and food cisterns. Removes tannins and traces of blood.

Operating temperature	35°C
Dosage	0,6 to 2 % (LP spray) 4 to 6 % (foam cannon)
Application time	15 to 20 min



REFERENCE	PACKAGING	WEIGHT
TN020090447	drum	25 kg
TN020090450	drum	240 kg
TN020090483	container	1200 kg

Biocide regulation n°528/2012 - N°MEEDDM : 7999

# MYCONET 03091

## SURFACE DISINFECTANT

Bactericide, fungicide and virucide surface disinfectant. Slightly foaming and wets easily. For disinfecting the interiors of warehouses, refrigerated lorries and food cisterns.

Operating temperature	Room temperature
Dosage	1 to 2,5 % (LP spray or foam cannon)
Application time	5 min



REFERENCE	PACKAGING	WEIGHT
TN030910447	drum	22 kg
TN030910450	drum	210 kg

Biocide regulation n°528/2012 - N°MEEDDM : 12548

# DDPA 02100

## DETERGENT DISINFECTANT OVER-ODORING

Disinfectant cleanser, over-odorant, food-grade, non-foaming, applicable by all systems: mop, auto-washer, spray, broom ... Guaranteed perfect hygiene of the treated surfaces.

Operating temperature	45°C
Dosage	2 to 4 %
Application time	15 min



REFERENCE	PACKAGING	WEIGHT
TN021000441	jerrycan	5 kg
TN021000447	drum	25 kg
TN021000450	drum	200 kg

Biocide regulation n°528/2012 - N°MEEDDM : 12548

# PE 03201

## DISINFECTANT CLEANER FOR ALL SURFACES

Disinfectant cleaner for all types of surfaces that can come into contact with foodstuffs. Very wetting and low foaming, has bactericidal and fungicidal properties. Especially suited for piping circuits.

Operating temperature	< 80°C
Dosage	0,5 to 2 %
Application time	5 to 15 min



REFERENCE	PACKAGING	WEIGHT
TN032010450	drum	200 kg
TN032010483	container	1000 kg

Biocide regulation n°528/2012 - N°MEEDDM : 25367

# PA 5 03221

## CONCENTRATED FOOD DISINFECTANT

Helps defeat bacteria, mold and parasitic fungi. Active from low temperature. Recommended for disinfecting, de-stemming ... and to treat harvesting machines, pumps, piping systems ... in the field of food.

Operating temperature	Room temperature
Dosage	0,1 to 2 %
Application time	15 min



REFERENCE	PACKAGING	WEIGHT
TN032210447	drum	22 kg
TN032210483	container	1100 kg

Biocide regulation n°528/2012 - N°MEEDDM : BC-JV034110-36



Use biocides with care. Always read the label and the product information before use.

## AF

02474

### FOOD DEGREASER, LOW FOAMING

Very strong alkaline degreaser for the degreasing of truck interiors, food tank. Low foaming detergent and very wetting, suitable for vats and to remove oils like rapeseed, palm, sunflower.

Operating temperature	Room temperature
Dosage	3 to 8 %
Application time	15 to 20 min



REFERENCE	PACKAGING	WEIGHT
TN024740446	drum	24 kg
TN024740450	drum	280 kg
TN024740483	container	1300 kg

## AFX

02682

### FOAMING FOOD DEGREASER

Degreaser for cleaning vegetable or animal fat residues. Also effective for stripping unpolymerized glues ... Very wetting, it is particularly suitable for tank interiors, tanks ...

Operating temperature	< 40°C
Dosage	1 % (aspersion) 5 % (foam canon)
Application time	5 to 20 min



REFERENCE	PACKAGING	WEIGHT
TN026820446	drum	21 kg
TN026820450	drum	240 kg
TN026820483	container	1000 kg

## LICA V2

052CO

### DEGREASER FOR TANK INTERIOR

Highly degreasing detergent powder for washing the inside of food tanks, containers, IBCs ... Easy dissolution and application on stainless steel, polypro, steels to remove oils, greases and fatty acids. Decouple uncooked paints.

Operating temperature	< 40°C
Dosage	2 to 5 %
Application time	5 to 10 min



REFERENCE	PACKAGING	WEIGHT
TN052B00181	bucket	15 kg
TN052C00108	bag	25 kg

## MECA FORTE

02638

### ULTRA-POWERFUL DEGREASER

Ultra-powerful alkaline degreasing renovator. Cleans fifth wheels, engines, chassis, tarpaulins, etc. Suitable for foam cannons. Not recommended for aluminium.

Operating temperature	Room temperature
Dosage	2 à 4 % (LP spray)
Application time	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN026380441	jerrycan	5 kg
TN026380447	drum	25 kg
TN026380450	drum	260 kg

## MECA SUP

05162

### FOAMING MECHANICAL DEGREASER

Highly concentrated, powerful degreaser, effective on soot, combustion residue, etc. Foaming alkaline product, can be used hot.

Operating temperature	40°C
Dosage	5 to 30 % (HP spray)
Application time	5 to 10 min



REFERENCE	PACKAGING	WEIGHT
TN051620441	jerrycan	5 kg
TN051620447	drum	25 kg
TN051620450	drum	230 kg

## D

05360

### NON-FOAMING DEGREASER

Non-foaming industrial alkaline degreaser. Can be used hot. Approved for contact with foodstuffs. Works well on the inside of refrigerators, chemical cisterns, mechanical parts and engines. Warehouses and aluminium and stainless steel equipment.

Operating temperature	50°C
Dosage	10 to 20 % (LP spray)
Application time	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN053600441	jerrycan	5 kg
TN053600447	drum	25 kg
TN053600450	drum	230 kg



# MECA D

05670

## NON-FOAMING MECHANICAL DEGREASER

Powerful scrubbing degreaser, can be used hot. Non-foaming industrial alkaline product for mechanical workshops. Effective on greasy floors, mechanical parts, engines removed from their housing, rims cleaning...

Operating temperature	50°C
Dosage	5 to 10 % (medium-pressure spray)
Application time	5 to 10 min

REFERENCE	PACKAGING	WEIGHT
TN056700441	jerrycan	5 kg
TN056700447	drum	25 kg
TN056700451	drum	70 kg
TN056700450	drum	230 kg

# DEG 3

ODEG3

## EMULSIFIABLE SOLVENT

Cold degreasing cleaner. Extremely powerful, for surfaces that have been heavily soiled by petroleum based products, etc. Water soluble.

Operating temperature	Room temperature
Dosage	20% to full strength (brush, sponge, or airless spray)
Application time	1 to 10 min
Flash Point	24°C

REFERENCE	PACKAGING	WEIGHT
TNODEG300441	jerrycan	5 l
TNODEG300447	drum	20 l
TNODEG300450	drum	200 l
TNODEG300483	container	1000 l

# DEG 4

05200

## DEGREASING EMULSIFIABLE SOLVENT

Odour-free tar-removing solvent. Can be used cold on any dirty surface, such as those soiled with tar, etc.

Operating temperature	Room temperature
Dosage	20% to full strength (brush, sponge, or airless spray)
Application time	1 min
Flash Point	60°C

REFERENCE	PACKAGING	WEIGHT
TN052000447	drum	22 l
TN052000450	drum	200 l



# DGO

C117

## MULTI-USE DEGREASER

Solvent free. Non-flammable, non-aggressive towards plastics, metals, rubbers and most paints. Very economical, for floors (auto-washer), mechanical parts, agricultural machinery. Especially effective for mixed deposits of sludge and grease ...

Operating temperature	< 80°C
Dosage	0,5 to 2 %
Application time	5 to 15 min

REFERENCE	PACKAGING	WEIGHT
C117/0001	can	1 l
C117/0005	jerrycan	5 l
C117/0030	drum	30 l
C117/0060	drum	60 l
C117/0210	drum	210 l

# NHO

C245

## HOT CLEANING

Detergent designed for cleaning high pressure hot water or brush tunnel equipment. Does not clog machine coils, causes scaling or crystallisation. Can be used cold.

REFERENCE	PACKAGING	WEIGHT
C245/0005	jerrycan	5 l
C245/0030	drum	30 l
C245/0060	drum	60 l
C245/0210	drum	210 l
C245/1000	container	1000 l

## NOVAL

**C067**

### SUPER ACTIVE ALUMINIUM RENOVATOR

Stripper, degreaser for aluminium and stainless steel surfaces. Renovates without rubbing, removes stains and makes the initial shine to aluminium and stainless steel. De-incrust, deoxidizes the weld seams, allows a passivation that favours the subsequent application of paints if needed.

Operating temperature	Room temperature
Dosage	renovation : ready to use degreasing : dilution 30 %
Application time	15 min

REFERENCE	PACKAGING	WEIGHT
C067/0005	jerrycan	5 l
C067/0060	drum	60 l
C067/0210	drum	210 l

## ALU WP +

**O11YO**

### PHOSPHOROUS-FREE DETERGENT

Phosphorous- and nitrogen-free acid detergent for the interior of cisterns. Restores the natural shine to aluminium, even after several washes. Suitable for cleaning LP tanks, cisterns, powder equipment, etc. Suitable for wash heads.

Operating temperature	60°C
Dosage	5 to 10 % (LP spray, wash heads)
Application time	5 to 10 min

REFERENCE	PACKAGING	WEIGHT
TN011Y00441	jerrycan	5 kg
TN011Y00446	drum	21 kg
TN011Y00450	drum	235 kg
TN011Y00483	container	1100 kg



## B

**O5110**

### CONCRETE STRIPPER

Concentrated concrete stripper. Cleans concrete mixing plant equipment, removes limescale and calcium deposits from all public works and construction equipment, floors, etc.

Operating temperature	40°C
Dosage	10 to 30 % (LP spray)
Application time	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN051100441	jerrycan	5 kg
TN051100447	drum	25 kg
TN051100450	drum	240 kg

## DECACIM

**O1200**

### BIODEGRADABLE CEMENT STRIPPER WITHOUT HCL

Cement cleaner / remover without hydrochloric acid, phosphoric, sulfuric ...  
Biodegradable, ready-to-use formula, non-corrosive for metals. Remove formwork oils and residues of laitance, cement, concrete ...

REFERENCE	PACKAGING	WEIGHT
TN012000441	jerrycan	5 kg
TN012000447	drum	25 kg
TN012000450	drum	200 kg
TN012000483	container	1000 kg

## HT 2002 P+

**O11PO**

### CONCENTRATED DESCALER

Ultra-concentrated acid renovator, ready to use. Cleans equipment soiled by lime, chalk, cement, slag, etc. Suitable for low and high pressure.

Operating temperature	40°C
Dosage	5 to 10 % (manual use or spray)
Application time	5 to 10 min



REFERENCE	PACKAGING	WEIGHT
TN011P00441	jerrycan	5 kg
TN011P00447	drum	25 kg

## OXYD

**O5090**

### DEOXIDIZING CLEANSER

Acid-based scrubbing cleaner that removes oxidation. Foaming descaler, effective on train/road containers, floors (refrigerated lorries). Tiled and painted floors. Formulated for aluminium: rims, rails, cisterns, etc. Suitable for galvanised steel, cement stains.

Operating temperature	40°C
Dosage	10 to 30 % (pulvérisation BP)
Application time	3 to 5 min



REFERENCE	PACKAGING	WEIGHT
TN050900441	jerrycan	5 kg
TN050900446	drum	24 kg
TN050900450	drum	270 kg
TN050900483	container	1300 kg
TN050910447	PAE (25%) drum	25 kg

# ACID

01032

## CLEANING SCRUBBER

Acid scrubber. Detergent with very strong wetting power. Interior cleaning for aluminium and stainless steel cisterns. Cleans aluminium rims and varnished or painted hub caps. Also removes deep-seated dirt from boat hulls.

Operating temperature	45°C
Dosage	5 to 10 % (LP spray)
Application time	5 to 10 min



REFERENCE	PACKAGING	WEIGHT
TN010320441	jerrycan	5 kg
TN010320446	drum	23 kg
TN010320450	drum	260 kg
TN010320483	container	1300 kg



# TAR REMOVING

## DEBIO

C330

### TAR REMOVING

Powerful emulsifiable powders remover based on plant extracts. Cleaning and degreasing of very dirty mechanical parts, combustion residues, oil and traces of tar and removes bitumen and its derivatives. Can also be used as anti-adherent and release agent: concrete, tar and elimination of asbestos glues. Without VOC, rinse with water.

REFERENCE	PACKAGING	WEIGHT
C330/0030	drum	30 l
C330/0210	drum	210 l
C330/01000	container	1000 l

## BITUME AC

C532

### ANTI-STICK COATED

Anti-adhesive for all bituminous products, odourless, methanol free, VOC free. Rapidly biodegradable, preserves its activity even in hot weather. Prevents the adhesion of draining or not, warm ecological coated ... and allows the protection of boots applicators, application equipment ... Keeps all its properties even during hot weather.

REFERENCE	PACKAGING	WEIGHT
C532/0005	jerrycan	5 l
C532/1000	container	1000 l

## NET BITUME

C421

### BITUMEN CLEANER AND ANTI-ADHESION

Cleaner and non-stick for bituminous products. Anti-stick, prevents the adherence of bitumen and asphalt on equipment and tools. Does not emit any VOC. Can be rinsed with water at the end of the operation. Easily biodegradable, compatible with fortuitous food contact, weak odor.

REFERENCE	PACKAGING	WEIGHT
C421/0005	drum	5 l
C421/0210	drum	210 l
C421/1000	container	1000 l

## BIOSOLV EXAM D-GEL

C335

### LOW VISCOSITY TAR REMOVING SOLVENT

Cleaning solvent based on plant extracts, biodegradable, new generation.

Flash Point	< 50°C
-------------	--------

REFERENCE	PACKAGING	WEIGHT
C335/0005	jerrycan	5 l
C335/0060	drum	60 l

## RENOV JANT 02633

### CONCENTRATED

Alkaline degreasing cleaner for rims of all vehicles. Efficiently removes brake pad dust and grease. Suitable for gantry cranes or high pressure terminals.

Application: spray, then 3 minutes of contact before brushing and rinsing HP.

Operating temperature	30°C maxi
Dosage	10 - 30 %

REFERENCE	PACKAGING	WEIGHT
TN026330441	jerrycan	5 kg
TN026330447	drum	25 kg
TN026330450	drum	260 kg

## JANT-NET 05222

### READY-TO-USE RIMS CLEANER

Degreasing cleaner for rims. Eliminates residue from brake pads, road film, etc.

Operating temperature	Room temperature
Dosage	100 % (LP spray)
Application time	3 to 5 min

REFERENCE	PACKAGING	WEIGHT
TN052220489	spray	750 ml

## TOUT-NET 0515

### READY-TO-USE MULTIPURPOSE CLEANER

Multi-purpose degreasing cleaner for all surfaces. Ready to use. Spray or wipe on soiled surfaces then rinse off.

Operating temperature	Room temperature
Dosage	100 % (LP spray)

REFERENCE	PACKAGING	WEIGHT
TN051520489	spray	750 ml
TN051500441	jerrycan	5 kg
TN051500447	drum	25 kg
TN051500451	drum	60 kg



## VIT NET 05026

### READY-TO-USE

Powerful degreasing cleaner, leaves no trace on media. Cleans glass and plastic surfaces. Spray at full strength and wipe with a clean cloth.

Operating temperature	Room temperature
Dosage	100 % (LP spray)

REFERENCE	PACKAGING	WEIGHT
TN050260489	spray	750 ml

## LAVE GLACE 05750

Windscreen washer fluid for all types of vehicles. pH neutral, does not attack windows, mirrors, plastics ... Cleans without leaving any residual traces or streaks. Use diluted or pure (up to - 20 ° C).

REFERENCE	PACKAGING	WEIGHT
TN057500447	drum	21 kg
TN057500451	drum	60 kg
TN057500483	drum	950 kg

## TS 3274

05510

### INDUSTRIAL FLOOR DETERGENT

Degreasing, non-foaming detergent with a natural solvent base. For concrete, resin, asphalt, or tiled floors. Removes wheel marks left by forklift trucks, etc. Leaves a long-lasting scent.

Operating temperature	Room temperature
Dosage	5 to 10 % (by hand, floor washer, HP)
Application time	5 to 10 min

REFERENCE	PACKAGING	WEIGHT
TN055100441	jerrycan	5 kg
TN055100447	drum	24 kg
TN055100450	drum	210 kg

## NEUTRALODOR 02360

### ODOR ELIMINATOR

Highly concentrated odour eliminator. Interiors of refrigerated lorries, food cisterns, rubbish skips, storage of rotting materials, water treatment plants, etc. Leaves no odour after use.

Operating temperature	Room temperature
Dosage	2 to 5 % (LP spray)
Application time	5 to 10 min



REFERENCE	PACKAGING	WEIGHT
TN023600441	jerrycan	5 kg
TN023600447	drum	24 kg
TN023600451	drum	62 kg

## OD

05210

### MASKING ODOURS

Scented cleaner. Used to mask odours. Contains alcohol for cleaning soiled carpet, ash trays, long vehicle/HGV cabs, offices, reception areas, and waste water drains that release unpleasant odours.

Operating temperature	Room temperature
Dosage	2 to 3 % (LP spray)
Application time	immediate

REFERENCE	PACKAGING	WEIGHT
TN052130489	flacon	250 ml
TN052100441	jerrycan	4 kg
TN052100451	drum	50 kg

## ANTITARTRE 04042

### PREVENTIVE ANTI-SCALING

Water treatment for high-pressure equipment that uses primarily hot water. A must-have product for the care and preventive maintenance of HP heat exchangers (coils). Very powerful, recommended for water with a TH > 10°C.

Operating temperature	Room temperature
Dosage	1 g/°TH/m3 (drop by drop)

REFERENCE	PACKAGING	WEIGHT
TN040420440	can	1 kg
TN040420450	drum	250 kg



## ORANGE CREME 5802

### CLEANING CREAM FOR HANDS

Solvent free, with pumice stone and plant-based ingredients. Thoroughly cleans without damaging the skin. For cleaning very dirty hands soiled with grease, mineral oil, soot, brake dust, etc. Apply to wet hands. Scrub well then rinse with water.

Operating temperature	Room temperature
Dosage	100 %

REFERENCE	PACKAGING	WEIGHT
25802J1	jerrycan	5 l

## TDD 935

### MINERAL ABSORBENT

Diatomaceous earth O5/10 used to rapidly absorb aqueous or hydrocarbon effusions. To prevent slipping, pollution ... Inert product that does not form sludge after absorption of liquids. Hydrocarbon absorption rate: 154%. Complies with AFNOR standard NFP 98.190 February 2002.

REFERENCE	PACKAGING	WEIGHT / VOLUME
8935H4	bag	20 kg / 40 l

## ABSOSOL R C653

### NON-MARKING MINERAL ABSORBENT

Attapulgite calcined with high absorption capacity for industrial floors, road networks, highways ... (Authorization of employment n° ABS.2001.04 delivered by the SETRA in conformity with the specifications of standard NF P 98-190). Avoids pollution, slips ... after spill. Do not stain the surfaces.

REFERENCE	PACKAGING	WEIGHT / VOLUME
C653/0015	bucket	15 kg / 25 l
C653/0020	bag	20 kg / 40 l



## ALGIFON 03025

### REINFORCED SHREDDER OF ALGAE AND LICHENS

Biocide treatment of algae, lichens ... on all surfaces, reinforced solution to be active on even porous surfaces: tiles, slates, fibre cement, bricks ... Does not stain the supports, is safe for garden furniture, sidewalks, walls ... Application: spray in dry weather.

Dosage	to be diluted to 25 %

REFERENCE	PACKAGING	WEIGHT
TN030250441	jerrycan	5 kg
TN030250447	drum	23 kg

## DETRUIMIXTE 05100

### READY-TO-USE

Ready-to-use biocide product to fight against algae, lichens ... on all media. Non-corrosive, very wetting, allows to quickly clear all treated surfaces. Perfectly adapted to facades, roofs, walls, statues, garden furniture ... in plastics, stones, marbles, glass ...

Operating temperature	15 to 40°C
Dosage	ready to use
Contact time	spray in dry weather

REFERENCE	PACKAGING	WEIGHT
TN051000441	jerrycan	5 kg
TN051000447	drum	23 kg



Use biocides with care. Always read the label and the product information before use.

## DOSATRON

### ASSAY SYSTEM

Allows precision dosing and mixing of two liquids. Works without electricity because it uses water pressure as a driving force. The concentrated product is sucked up and dosed at the desired percentage and then homogenized. The highly accurate dosage eliminates any risk of overdose because it is constant and proportional to the volume of water passing through the dispenser (insensitive to changes in pressure and flow).



REFERENCE	
TN1117608090	DOSATRON D25 RE 10 + dosing and spraying kit
TN1117648090	DOSATRON D25 RE 10 (nu)
TN1122809090	DOSATRON D07 RE 5 (nu)

## BRUSH BLACK BOOSTER

### NEW GENERATION GUN WITH MOTOR ON BALL BEARING

Adjusting the compressed air pressure built into the gun  
 - Removable brush: prevents the dispersion of dirt during cleaning. New 360° angled connection for compressed air: even when connected, the gun can be placed on a worktop. Comfort of use, the compressed air hoses do not bend anymore.  
 - New reinforced cap: double screw pitch, allows to use the original gun container or any other bottle with a 28/400 neck thread.  
 Recommended detergent: Transnet TOUT-NET (p.12)



Pressure	6,5 bar
Power	5000 RPM

REFERENCE	
TN1972DVG8090	Flexible double
TN1972DVH8090	BRUSH BLACK BOOSTER
TN1972DVI8090	EXTRACTOR + 4 ADAPTERS

## TRANSLAV DV

DV Translav allows spray diffusion of a pre-dosed product on the surfaces to be treated. The DV Translav is supplied with hose, lance and nozzle pockets.

### TECHNICAL CHARACTERISTICS

Water supply pressure at the inlet of the appliance:

1.5 bar (minimum) 6 bar (maximum)

Maximum suction height product:

2 meters.



REFERENCE	
TN1972DV08090	TRANSLAV DV full
TN1972DV48090	TRANSLAV Box (without lance or hose)
TN1972DV18090	Telescopic lance 2 m with handle
TN1972DV78090	25 m Armed Hose
TN1972DV58090	Poch. TRANSLAV sprinklers
TN1972DV58090	Polypropylene handle TRANSLAV

## MANUAL SPRAYER

Application of cleaning products, disinfectants, shampoos for vehicles ...

REFERENCE		CAPACITY
TN1 972PUL 0 80 90	LASER 2 sprayer	1,5 l
TN1 1139 0 80 90	LASER 8 sprayer	5 l
TN1 972G10 0 80 90	LASER 10 sprayer	8 l



## GRADUATED PITCHER

Graduated pitcher of 1l.  
 Ideal for the dilution of products.

REFERENCE	QUANTITY
LB 922460	1 pitcher



## MANUAL BARREL PUMP MAJOR

Manual barrel pump made of polyethylene.  
 Suitable for solvent transfer, antifreeze, aqueous solution ...

REFERENCE	VOLUME
TN1102508090	100 ml



## BUFF INDUSTRIAL COIL

2-folds Buff industrial coil  
 1500 formats of 23 x 23 cm

REFERENCE	PACKAGING
83114B0B	package of 2 reels



## BUFF INDUSTRIAL COIL

2-folds Buff industrial coil  
 800 formats of 23 x 23 cm.

REFERENCE	PACKAGING
83115B0B	package of 2 reels

## TRANSNET COMBINAISON

Integral combination for protection during spraying.  
 Fitted waist, removable sleeves, water repellent treatment.

RÉFÉRENCE	SIZE
TN185108090	size 60



## INDIVIDUAL COMBINATION AR0109

### INDIVIDUAL PROTECTION EQUIPMENT

Combination HOP'SAFE SMS with PE membrane hood.  
 Waterproof and breathable membrane, lint-free combination.  
 Good resistance to tearing and abrasion.

REFERENCE	PACKAGING
AR0109-L	Cardboard of 25 combinations
AR0109-XL	Cardboard of 25 combinations





## WASHING BRUSH WATERFED

**TN524752**
**HIGH/LOW, 280 mm, SOFT/SPLIT, BLACK**

The angled design of this wash brush enables the brush to be in constant contact with surfaces during washing, even when cleaning in height. Rubber edges to avoid any risk of shock. Fits on all Vikan sleeves.



## VEHICLE BRUSH WATERFED

**AR7080**
**370 mm, SOFT/SPLIT, BLACK**

Oval brush with water passage, 370 mm. This large brush is particularly suitable for cleaning large vehicles. The density of the flowered fibers makes it even more effective. Rubber edges to avoid any risk of shock. Fits on all Vikan sleeves.



## VEHICLE BRUSH WATERFED

**VIK525452**
**360 mm, SOFT/SPLIT, BLACK**

Hand brush with water passage equipped with a Gardena connector. Ideal for small cleaning tasks.



## RIM CLEANER

**VIK525352**
**Ø65 mm, 335 mm, HARD, BLACK**

Rigid rim brush, 65 mm. Effective for cleaning aluminium rims.



## ALUMINIUM TELESCOPIC HANDLE

**TN297552**
**1575 - 2780 mm, Ø32 mm, BLACK**

Ergonomic and telescopic handle in aluminium, 2800mm. Made of aluminium and heavy-duty shockproof plastic for a good grip, this ergonomic handle allows a pleasant and functional use.



## ALUMINIUM TELESCOPIC WATERFED HANDLE

**AR7082**
**1600 - 2780 mm, Ø31 mm, BLACK**

Ergonomic and telescopic aluminium handle with water connection and quick coupling, 2840 mm. Made of aluminium and heavy-duty shockproof plastic for a good grip, this ergonomic handle allows a pleasant and functional use.



## WALL BRACKET

**7010N**
**4-6 PRODUCTS 395 mm, BLACK**

Support available in full colour code. You can enlarge the support by attaching a second support. You can also change the location of the rubber hooks and clips.

Easy to clean by simply dismantling the different parts. The rubber clip can accommodate Ø25-35 mm tools.



## RIM CLEANER WATERFED

**VIK545252**
**240 mm, SOFT/SPLIT, BLACK**

Particularly suitable for truck wheels, coaches, buses ...



All VIKAN materials and accessories are compatible with each other.

# ALPHABETICAL INDEX

PRODUCT	REFERENCE	FAMILY	PAGE
ABSOSOL R	C653	WASH STATION MAINTENANCE	14
ACID	01032	RENOVATORS	11
AF	02474	DEGREASERS	8
AFX	02682	DEGREASERS	8
ALGIFON	03025	WASH STATION MAINTENANCE	14
ALU WP +	011Y0	RENOVATORS	10
ALUMINIUM TELESCOPIC HANDLE	TN297552	MATERIALS	17
ALUMINIUM TELESCOPIC WATERFED HANDLE	AR7082	MATERIALS	17
ANTITARTRE	04042	WASH STATION MAINTENANCE	13
B	05110	RENOVATORS	10
BACTIMOUSS	02089	TECHNICAL CLEANING - FOOD RANGE	7
BIOSOLV EXAM D-GEL	051V0	TAR REMOVING	11
BITUME AC	C532	TAR REMOVING	11
BRUSH BLACK BOOSTER	TN1972DV	MATERIALS	15
BUFF INDUSTRIAL COIL	83114B0B	MATERIALS	16
BUFF INDUSTRIAL COIL	83115B0B	MATERIALS	16
C +	05300	SHAMPOOS	4
C SUPER	05060	SHAMPOOS	4
D	05360	DEGREASERS	8
DDA	02009	TECHNICAL CLEANING - FOOD RANGE	7
DDPA	02100	TECHNICAL CLEANING - FOOD RANGE	7
DEBIO	C330	TAR REMOVING	11
DECACIM	01200	RENOVATORS	10
DEG 3	0DEG3	DEGREASERS	9
DEG 4	052Q0	DEGREASERS	9
DETRUIMIXTE	05100	WASH STATION MAINTENANCE	14
DGO	C117	DEGREASERS	9
DOSATRON	TN11	MATERIALS	15
GRADUATED PITCHER	LB 922460	MATERIALS	15
HT 2002 P+	011P0	RENOVATORS	10
INDIVIDUAL COMBINAISON	AR0109	MATERIALS	16
JANT-NET	052Z2	WORKSHOP	12
LAVE GLACE	05750	WORKSHOP	12
LC	05300	TECHNICAL CLEANING - FOOD RANGE	6
LICA V2	052C0	DEGREASERS	8
MANUAL BARREL PUMP MAJOR	TN1102508090	MATERIALS	15
MANUAL SPRAYER	TN1	MATERIALS	15
MECA D	05670	DEGREASERS	9
MECA FORTE	02638	DEGREASERS	8
MECA SUP	05162	DEGREASERS	8
MYCONET	03091	TECHNICAL CLEANING - FOOD RANGE	7
NET BITUME	C421	TAR REMOVING	11
NEUTRALODOR	02360	WASH STATION MAINTENANCE	13
NHO	C245	DEGREASERS	9
NOVAL	C067	RENOVATORS	10
NVA	05600	TECHNICAL CLEANING - FOOD RANGE	6
NVA +	051U0	TECHNICAL CLEANING - FOOD RANGE	6
OD	05210	WASH STATION MAINTENANCE	13
ORANGE CREME	5802	WASH STATION MAINTENANCE	14
OXYD	05090	RENOVATORS	10
PA5	03321	TECHNICAL CLEANING - FOOD RANGE	7
PE	03201	TECHNICAL CLEANING - FOOD RANGE	7
PLATINIUM	05050	SHAMPOOS	4
PROCAR AT	C441	SHAMPOOS	5
RENOV JANT	02633	WORKSHOP	12
RIM CLEANER	VIK525352	MATERIALS	17
RIM CLEANER WATERFED	VIK545252	MATERIALS	17
S	05409	SHAMPOOS	5
S +	0506W	SHAMPOOS	4
SA	05604	TECHNICAL CLEANING - FOOD RANGE	6
SA +	051V0	TECHNICAL CLEANING - FOOD RANGE	6
SCM	05169	SHAMPOOS	5
SGC	05400	SHAMPOOS	4
TAM	01171	SHAMPOOS	5
TDD	935	WASH STATION MAINTENANCE	14
TOUT-NET	0515	WORKSHOP	12
TRANSLAV DV	TN1972DV08090	MATERIALS	15
TRANSNET COMBINAISON	TN185108090	MATERIALS	16
TS	05032	SHAMPOOS	5
TS 3274	05510	WASH STATION MAINTENANCE	13
VEHICLE BRUSH, WATERFED	AR7080	MATERIALS	17
VEHICLE BRUSH, WATERFED	VIK525452	MATERIALS	17
VIT NET	05026	WORKSHOP	12
WALL BRACKET	7010N	MATERIALS	17
WASHING BRUSH, WATERFED	TN524752	MATERIALS	17

# OUR PRESENCE IN THE WORLD



## FRANCE



Parc Industriel de la Plaine  
de l'Ain - 225, allée des Cèdres  
01150 Saint-Vulbas - FRANCE

Tel.: + 33 (0)4 74 40 20 00

Fax: + 33 (0)4 74 40 20 01

Web: www.orapi.com

Email: contact@orapi.com

### EXPORT DEPARTMENT

Tel.: 33 (0)4 74 40 20 25

Fax: 33 (0)4 74 40 20 26

Email: export@orapi.com

## NORTHERN EUROPE

### BELGIUM

#### ORAPI APPLIED BELGIUM S.A

Kapelsesteenweg 292  
2930 Brasschaat  
Tel.: +32 2 2800 736  
Email: sales@orapiapplied.be

### NORWAY

#### ORAPI APPLIED NORWAY

Pb 1573 - 4688 Kristiansand  
Tel.: +47 333 66 000  
Fax: +47 333 66 008  
Email: kundeservice@orapi.no

### UNITED KINGDOM

#### ORAPI APPLIED Ltd

Spring Road, Smethwick  
West Midlands, B66 1PT  
Tel.: +44 121 525 4000  
Fax: +44 121 525 4919  
Email: info@orapiapplied.com

### FINLAND

#### ORAPI NORDIC OY AB

Salpakuja 6 - 01200 Vantaa  
Tel.: +358 9 894 6430  
Fax: +358 9 8946 4322  
Web: www.orapinordic.net  
Email: sales@orapinordic.net

### NETHERLANDS

#### ORAPI APPLIED NEDERLAND B.V

Ondernemingsweg 16  
2404 HN Alphen aan den Rijn  
Tel.: +31 172 43 72 21  
Fax: +31 172 43 69 01  
Web: www.orapiapplied.nl  
Email: sales@orapiapplied.com

### POLAND

#### ORAPI TRANSNET Sp. z o.o.

ul. Sremska 75a - 62-050  
Mosina Tel.: +48 61 813 86 40  
Fax: +48 61 813 86 91  
Email:  
mariusz.polkowski@orapi.com

### SWEDEN

#### ORAPI NORDIC OY AB

Vaksala - Eke Hus C  
755 94 Uppsala  
Tel.: +46 18 506 010  
Fax: +46 18 500 910  
Web: www.orapi.se  
Email: info@orapi.se

## SOUTHERN EUROPE

### ITALY

#### ORAPI ITALIA Srl

Via Vaccarella 39  
00071 Pomezia (RM)  
Tel.: +39 06 916 10576  
Fax: +39 06 918 02468  
Email: info@orapi.it

### SPAIN

#### ORAPI TRANSNET

ESPAÑA, SL  
C/Secorún nº 4  
22600 Sabiñánigo (Huesca)  
Tel./Fax: +34 974 480 828  
Email: adminote@orapi.com

## AMERICA

### CANADA

#### ORAPI CANADA Ltd

7521 Henri Bourassa Est  
Montréal - Québec H1E1N9  
Tel.: +1 514 735 32 72  
Fax: +1 514 735 85 50  
Email: jean.falouey@orapi-  
canada.com

### MARTINIQUE

#### ORAPI HYGIENE MHE

Immeuble Diana ZI Cocotte  
Canal 97224 Ducos  
Tel.: 0596 77 37 07  
Fax: 0596 77 37 08  
Email: info@mhe-martinique.com

## ASIA & MIDDLE EAST

### SINGAPORE

#### ORAPI APPLIED (S) Pte Ltd

No. 26 Tuas Avenue 13  
Singapore 638992  
Tel.: +65 6265 2888  
Fax: +65 6268 6474  
Email: sin.sales@orapi.com.sg

### THAILAND

#### ORAPI APPLIED (T) Co. Ltd

55/75 Moo 9, Townplus Kaset  
Nawamin Village, Klonglumjiak  
Road, Klongkum, Buengkum,  
Bangkok 10240 - Thailand  
Tel.: +66 2 508 1342  
Fax: +66 2 508 1343  
Email: info@ccsthailand.com

### MALAYSIA

#### ORAPI APPLIED (M) Sdn Bhd

No. 10, Jalan PJU 3/49  
PJU 3, Sunway Damansara  
47810 Petaling Jaya - Selangor,  
Malaysia  
Tel.: +60-3-7805 3805  
Fax: +60-3-7880 5805  
Email: msia.sales@orapi.com.my

## UNITED ARAB EMIRATES

#### ORAPI MIDDLE EAST L.L.C.

729 Business Village Main Bldg B -  
PO Box 120509, Dubai  
United Arab Emirates  
Tel: +971 (0) 42942947  
Fax: +971 (0) 42942948  
Email: dxb.sales@orapi.ae

## PACIFIC

### AUSTRALIA

#### VICTORIA LUB Pty Ltd

Factory 24, 29-39 Kirkhan Road  
West Keysborough, Po Box 816  
Victoria 3174  
Tel.: +613 9701 5373  
Fax: +613 9701 5532  
Email: info@viclub.com.au

## TAHITI/FRENCH POLYNESIA

### TALLIN PI

BP4045, Papeete 98713,  
Polynésie française  
Tel.: +689 40 82 48 58  
Email: tpid@mail.pf

## NEW CALEDONIA

#### SFAC Sarl

27, rue Ampère - ZI Ducos - BP  
3725 98846 Nouméa Cedex  
Tel.: +687 77 72 19  
Fax: +687 27 20 67  
Email: sfac@sfac.nc

## AFRICA

### MAURITIUS

#### PROLUB Cie Ltd

62 Pailles Road - Port Louis  
Tel.: +230 286 6328  
Fax: +230 286 6330  
Email: admin.prolub@intnet.mu

## SOUTH AFRICA

#### ORAPI AFRICA Ltd

228 Albert Amon Road - Millenium  
Business Park - Meadowdale Ext.  
7 1609 Gauteng  
Tel.: +27 (0) 11 454 51 38  
Fax: + 27 (0) 11 453 11 84  
Email: info@orapiafrica.co.za



Parc Industriel de la Plaine de l'Ain  
225, allée des Cèdres  
01150 Saint-Vulbas - FRANCE

Tel. : + 33 (0)4 74 40 20 25 - Fax : + 33 (0)4 74 40 20 26  
[contact@orapi.com](mailto:contact@orapi.com)