

TRANSNET DEG3

TAR REMOVER

DESCRIPTION

TRANSNET DEG3 is an emulsifiable tar removing solvent for engines and mechanical parts. The presence of surfactants makes it very effective for combating petroleum grease deposits.

TRANSNET DEG3 is a mixture of organic solvents particularly suitable for degreasing operations which require short drying time. It deeply penetrates the bituminous deposits to be removed.

TRANSNET DEG3 is recommended for cleaning equipment and materials in contact with asphalt or tar.

TRANSNET DEG3 can be used on all substrates, including painted.

APPLICATION/INSTRUCTIONS FOR USE

Apply for 1 minute at room temperature.

Use pure or diluted in 3 to 5 volumes of water thanks to its emulsifying properties;

TRANSNET DEG3 can be applied manually with a brush, sponge or cloth, or airless spray.

Rinsed with cold water.




When handling the product and parts, we recommend wearing solvent-resistant protective gloves.

CHARACTERISTICS

Aspect:Clear liquid
pH (pure product):Not applicable
pH at 10 g/l:Not applicable
Density at 20°C:0.87 +/- 0.02 g/cm³
Freezing point:-10°C
Flash point:24°C
Colour:Colourless

The surface agents used in the design of our products comply with biodegradability criteria as defined in EC regulation No. 648/2004 relating to detergents.

PACKAGING

**20 kg****174 kg****870 kg**

STORAGE

Store the product in a dry location in its original packaging.

To view the product's safety data sheet: www.quickfds.com – access code TRA11